



MULTI-ADAPTER MODEL EJ-10

handles virtually
any input signal

includes all audio
connections

no power supply
required

telephone line
input capability

The Model EJ-10 is a multi-input adapter that accepts line or speaker level input from a variety of audio/video devices, including an analog telephone. It then inserts the signal into an existing PA or music system, while providing the necessary matching and isolation protection for the sound system.

The EJ-10 provides everything required to connect a telephone, VCR, phonograph, tape player, guitar, projector, PC, CD player, DVD player, radio or other audio source, to the microphone input of a PA system. Virtually any input signal can be accommodated, including a speaker level input of up to 10 watts.

The EJ-10 is a completely passive device, no batteries or external power sources are required for operation.

The EJ-10 features a volume control, RJ-11 modular jacks, phone and phono jacks, a hum switch, and a telephone seize switch. In the telephone line mode, the EJ-10 seizes the telephone line for continuous use. An assortment of interconnect cables and a nylon pouch come attached to the unit. Basic instructions and a block diagram are imprinted on the front panel. A complete instruction manual comes stored inside a pocket of the carrying case.

Specifications:

Inputs	Unbalanced line level / Speaker level (1/8" & 1/4" mono/stereo phone, and RCA phono jacks. Telephone line - RJ11 modular jack in accordance with FCC regulation No.E8P51E71393-VP-N; Ringer Equivalence: 0.38.)
Outputs	Transformer balanced, adjustable mic level (3' cable with male XLR plug. Telephone line uses RJ11 modular jacks.)
Attenuation	Line levels = -22dB to -93dB Speaker level = -53dB to 100dB Telephone = -16dB to -65dB
Frequency Response	Speaker/Line = 20Hz to 20kHz Telephone= 60Hz to 3.5kHz
Package	Aluminum case with a polycarbonate overlay in a gray Cordura nylon pouch with zipper.
Dimensions (L x W x H)9.0" x 6.5" x 3.0"
Weight	2 lbs.

Architects'/Engineers' Specifications:

The Multi-Adapter box will accept mono or stereo line and speaker level inputs, and will allow a seized connection to the local telephone system; converting all of the signals to a transformer balanced mic level output. The adapter box must have an adjustable output control and a hum removal switch. All interconnect cables must be attached to the unit, and a padded zippered case must be provided for protection and for transporting the unit. Basic instructions with a block diagram must be imprinted on the front panel, and an operations manual must be stored in the carrying case. The size must be 9.0" L X 6.5" W X 3.0" H, and its weight should be 2 lbs. The multi-adapter box will be an Emtech Model EJ-10.

Warranty:

Emtech Electronics, Inc. warrants the Model EJ-10 for a period of two years, from the original date of purchase, against defects in parts and workmanship. If a defect occurs, the unit will be repaired or replaced, at our option, free of all charges if delivered prepaid to the factory. Warranty does not extend to finish, appearance, abuse or defects due to misuse or operation under other than specified conditions, nor does it extend to incidental or consequential damages. Repair by anyone other than Emtech will void the warranty.